## Thomas&Betts



Project: CED Location: houston

ced

## Dynamic Braking / DC Drive T&B Catalog Number:

UPC Number: Status: Description: EHDB220C-1L 66201943943 Active

3 pole, 2 NO and 1 NC, plus 1 NO and 1 NC auxiliary contacts, 220 amp, DC drive, dynamic breaking contactor, with a 120V AC coil **Features** 

	Double-break contacts with magnetic arc chutes
	Elevator service rated
Standards	
	cULus
Application	
	For use with solid state DC adjustable speed drive
	systems
General	
Cariaa	
Series	EHDB
Poles	2 NO and 1 NC
Coil Type	AC
Auxiliary Contacts	1 NO and 1 NC
Dimension Information	
H x W x D (inches)	7.79 x 5.83 x 6.65
Specifications	
Coil Voltage	120V AC
DC Continuous Current (A)	220
DC Power Pole Make/Break Voltage (V)	600
DC Power Pole Make/Break Current (C)	333
DC Dynamic Braking Pole Make Voltage (V)	600
DC Dynamic Braking Pole Make Current	450
(A)	
DC Dynamic Braking Pole Break Voltage	300
(V)	
DC Dynamic Braking Pole Break Current	285
(A)	
Packaging	
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	10.65 lbs. Each

For further technical assistance, please contact us...



8155 T&B Blvd. Memphis, TN 38125 www.tnb.com MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com