



Split-Bolt

T&B Catalog Number:

40H

UPC Number:

78378620017

Status:

Active

Description:

Type H - High Strength Split-Bolt Connector, Conductor Range for Equal Main and Tap 250 kcmil-1 Str, Conductor Range for Min Tap with One Max Main 8 Sol

Features

Bolt and nut of high-strength corrosion-resistant bronze alloy. Copper pressure bar. Bolt and nut of hex design.

Standards

UL, CSA

Application

Splicing, tapping or terminating conductors in power and grounding electrical connection.

General

Style Type H

Wire Type Copper

Material Bronze Alloy

Color Metallic

Conductor Range for Equal Main and Tap 250 kcmil-1 Str.

Conductor Range Min. Tap with one Max. 8 Sol.

Main

Dimension Information

A (inches)	1
B (inches)	0.580
C (inches)	1 5/16
D (inches)	2 5/32

Packaging

T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	36.5 lbs. per 100

Notes

UL recognizes solid and stranded conductor configurations for sizes #8 and smaller and stranded configurations only for sizes #6 and larger.

Certifications

RoHS Compliance Yes

Certifications



File Nbr:

E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com