



# ATLAS 830

## Integrated Access Device

### Product Features

- Supports T1, T3, ISDN PRI/BRI, IP Routing, and Frame Relay networks
- Eight-slot modular chassis includes 2 T1/PRI ports and a 10/100Base-T Ethernet port
- Option modules are hot-swappable
- Supports voice and data over Frame Relay applications and offers optional Dial Backup
- Integral Switchboard and Dial Plan for intelligent call-by-call routing, number substitution, and protocol conversion
- Supports NxT1 Inverse Multiplexing over T3 or multiple T1s
- Supports 3/1/0 Digital Cross Connect applications
- Ideal WAN access switch for videoconferencing
- Supports PRI delivered over T3
- AC and -48 VDC versions
- Industry-leading five-year North American warranty

**The ADTRAN® ATLAS™ 830 Integrated Access Device (IAD) is a multi-function, modular platform that provides voice, data, video, and Internet connectivity and WAN access to reduce overall telecommunication expenses.** The ATLAS 830 is designed to be installed between the network service provider's circuit(s) and customer premises equipment enabling many network devices to share WAN access and bandwidth. This flexible and modular platform functions as a T1/T3/E1 bandwidth manager, ISDN PRI/BRI switch, Frame Relay switch, IP Router, NxT1 IMUX, and 3/1/0 DACS. It also includes intelligent call routing through the integral switchboard and dial plan that provides dynamic call-by-call switching based upon the called or calling phone number.

The ATLAS 830 is an eight slot, modular platform that supports up to 34 T1/PRI or 32 E1s and offers a series of hot-swappable option modules, allowing the system to satisfy many applications in corporate networks. The ATLAS 830 chassis includes two independent software programmable network interfaces that can be configured for T1, DSX-1, or PRI operation.

The ATLAS 830 provides DACSing and grooming for T3 and T1 circuits in a small and economical footprint. Users can perform time slot interchange and reassign or cross-connect any DS0 from any circuit to any other circuit.

The ATLAS 830 also provides dynamic circuit switching on the high speed backplane. ISDN and voice switching are performed on a call-by-call basis for on-premises routing or least cost routing to the public network.

The ATLAS 830 supports video applications by providing multiple T1, PRI, BRI, V.35, RS-449, EIA-530 and RS-366 interfaces for codecs and gateways. By using the Nx56/64 BONDing module, video calls ranging from 112 kbps up to a full PRI rate (1.472 kbps) can be supported.

For data applications, users can connect the ATLAS 830 directly to the LAN using the integral 10/100Base-T Ethernet interface and internal IP routing software. Users can also connect an external router or other device through one or more serial ports. ATLAS 830 offers a variety of serial interface options, including V.35, EIA-232, EIA-530, RS-449, X.21, and V.36. The ATLAS 830 includes Frame Relay software as well as an IP router and support for PPP applications.

Voice over Frame Relay (VoFR) is supported using one or more of the optional Voice Compression Modules to deliver high quality voice among Frame Relay sites. The ATLAS 830 can be configured to transport voice and data traffic within a single PVC, reducing monthly expenses. An ATLAS 830 can be optioned to transport up to 64 compressed voice connections over a Frame Relay network. ATLAS 830 supports IP routing over public and private Frame Relay networks.

For network management, the ATLAS 830 supports N-Form® and offers local and remote management capabilities using Telnet or VT100 connected to the built-in 10/100Base-T Ethernet interface. The ATLAS 830 also includes LEDs for complete operational status indications.



ADTRAN, Inc.

Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000 voice  
256 963-8699 fax  
256 963-8200 fax back

**General Information**  
800 9ADTRAN  
info@adtran.com  
www.adtran.com

**Pre-Sales  
Technical Support**  
800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

**Where to Buy**  
877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

**Post-Sales  
Technical Support**  
888 423-8726  
support@adtran.com  
www.adtran.com/support

**ACES Installation &  
Maintenance Service**  
888 874-ACES  
aces@adtran.com  
www.adtran.com/support

**International Inquiries**  
256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/international

**For the regional office  
nearest you, visit:**  
www.adtran.com/where2buy



ADTRAN is an  
ISO 9000: 2000 certified supplier.



ADTRAN is a  
TL 9000 3.0 certified supplier.

61200780L1-8B April 2003  
Copyright © 2004 ADTRAN, Inc.  
All rights reserved.

# ATLAS 830

## Integrated Access Device

## Product Specifications

### Network Interface

- Two built-in T1/DSX-1/PRI ports
- Full or Fractional T1 support
- Connects to carrier or CPE equipment; software configurable
- Built-in CSU

### ISDN PRI

- Lucent 4E/5E, DMS 100, and National ISDN protocols

### T1 Line Rate

- 1.544 Mbps +/- 75 bps

### T1 Physical Interface

- RJ-48C: Modular, 8-pin

### T1 Framing

- D4(SF), ESF

### T1 Line Code

- AMI, B8ZS

### T1 Input Signal

- 0 to -36 dB

### T1 Line Length

- DS-1:6000 ft (24 AWG)
- DSX-1:665 ft

### LAN Features

- Built-in 10/100BaseT Ethernet management port

### Physical

- **Dimensions:** 17.5" W x 12.5" D x 5.5" H
- **Weight:** 15 lbs
- **Power:** 50 W (base unit)
- **Current:** 4 amps
- **Agency Approvals:** UL 60950, CUL, FCC Part 15 (Class A), and FCC Part 68
- **Operation:** 0°C to 45°C
- **Storage:** -40°C to 70°C

### Frame Relay Specifications

#### Frame Relay

- RFC 1490 encapsulation

#### Link Management

- ANSI T1.617-D (Annex D)
- ITU-T Q.933-A (Annex A)
- LMI (group of four)
- Automatic link management protocol discovery

#### Congestion Control

- FECN/BECN, Discard Eligible (DE)

#### Quality of Service

- User configurable DLCI priorities

#### Route Management

- RIP V1, RIP V2, ICMP, ARP, IARP, UDP Relay

#### Management Features

- Configuration using Telnet
- Trap/Alarm messages using SNMP
- N-Form software provides extensive management including front/rear panel images, trap/alarm messages, and customizable reports
- Alarm contacts

#### Product Includes

- ADTRAN utilities software (includes TFTP server, VT100 client, Telnet); two RJ-48C straight-through cables; one RJ-48C crossover cable; one RJ-48-to-DB-15 adapter; user manual, and 19" mounting brackets.

## Ordering Information

Equipment	Part #
ATLAS 830, AC	1200780L1
ATLAS 830, DC	1200781L1



Specifications subject to change without notice. ATLAS is a trademark of ADTRAN, Inc. ADTRAN and N-Form are registered trademarks of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.