EN4200 Serial Receiver

www.boschsecurity.com





The EN4200 Serial Receiver is a gateway between security transmitters and a Bosch Security Systems, Inc. control panel. The EN4200 decodes radio frequency (RF) transmissions from end devices and high-power repeaters, and then outputs the data to the panal via a wireless interface module.

System overview

Powered by Inovonics

The Inovonics EchoStream platform, powered by Inovonics wireless mesh network technology, ensures superior range, reliability, and scalability for commercial applications. Using a wide range of transmitters and repeaters, this proven technology provides flexibility and performance to meet the most stringent requirements. This exclusive protocol is available only on Inovonics EchoStream products.

Wireless 900 MHz Band

The Inovonics EchoStream platform sends redundant information on several multi-frequency channels within the FCC Part 15 900 MHz band, providing superior range and reliability. In comparison, systems that use a single frequency technology can only send information on one narrow band channel. Any interference within the band can cause missed signals. With wireless registration, it is easy to add this technology to any application.

- Decoding of RF transmissions for use by the interface and control panel
- Uses reliable frequency-hopping, spread-spectrum technology
- Serial integration with hundreds to thousands of wireless devices

Functions

Wireless Registration

There is no external programmer required. The transmitter is enrolled using a wireless programming routine built into the receiver. Wireless registration reduces installation time.

Secure Wireless Implementation

Jam detection monitors all channels for the presence of interference for more than 20 seconds. A reset terminal is inside the receiver, allowing the receiver to accept external reset signals. The receiver Includes a case tamper and internal antennas for added security.

Supervision and Expansion

Transmitter supervisory check-in and a transmitter specific supervisory window, defined in the receiver, support sites with both removable pendants and fixedposition transmitters. The technology also supervises repeaters.

Certifications and approvals

Inovonics Wireless Corporation holds the following approvals:

FCC Conforms to FCC Part 15 regulations

Installation/configuration notes

Compatibility Information

The EN4200 Serial Receiver is compatible with the following products:

Control Panels

All versions of the D9412GV4, D9412GV3, D9412GV2, and D9412G

All versions of the D7412GV4, D7412GV3 and D7412GV2; v6.30 or higher of the D7412G

All versions of the D7212GV4, D7212GV3 and D7212GV2; v6.41 or higher of the D7212G

Wireless Interface Module

B820	SDI2 Inovonics EchoStream Interface Module
ISW-D8125CW-V2	Zonex Inovonics EchoStream Interface Module

Repeaters

EN5040-T

Transmitters

All Bosch Security Systems, Inc. Inovonics EchoStream transmitters

High-power Repeater

Parts included

1 EN4200 Serial Receiver

Technical specifications

Electrical

Power:

10 to 14 V, 100 mA

Environmental

Relative Humidity:	Up to 90%, non-condensing
Temperature (operating):	0°C to +60°C (+32°F to +140°F)

Mechanical

Dimensions:	16.2 cm x 9.4 cm x 2.8 cm (6.4 in. x 3.6 in. x 1.1 in.)
Weight:	133 g (4.7 oz)

Reception Characteristics

Frequency Compatibility:	Frec	uency	Compati	bility:
--------------------------	------	-------	---------	---------

901 MHz to 928 MHz

Trademarks

Trademark names are used throughout this document. In most cases, these designations are claimed as trademarks or registered trademarks in one or more countries by their respective owners. Rather than placing a trademark symbol in every occurrence of a trademark name, Bosch Security Systems, Inc. uses the names only in an editorial fashion and to the benefit of the trademark owner with no intention of infringing the trademark.

Inovonics is a trademark of Inovonics Wireless Corporation.

Ordering information

EN4200 Serial Receiver

Contains EN4200 Serial Receiver. Order number **EN4200**

Accessories

Zonex Interface and Receiver Kit

Kit containing ISW-D8125CW-V2 and EN4200 for use on Zonex bus G Series panels. Order number **ENKIT-01**

SDI2 Inovonics Interface and Receiver Kit

Kit containing B820 and EN4200 for use on SDI2 bus panels.

Order number ENKIT-SDI2

Represented by:

Americas:

Americas: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 280 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

@ Bosch Security Systems 2013 | Data subject to change without notice 2578326027 | en, V4, 01. Oct 2013

Asia-Pacific:

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2609 apr.securitysystems@bosch.com www.boschsecurity.asia

China:

China: Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.bacsbecurity.com.cn www.boschsecurity.com.cn

America Latina:

America Latina: Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 Iatam.boschsecurity@bosch.com www.boschsecurity.com