

# LECTUS duo 3000 EV1 line

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Two interfaces - RS485 and Wiegand
- ▶ Reader for MIFARE Desfire EV1
- ▶ Water and weather resistant - IP65
- ▶ Wall or mullion mount
- ▶ Tamper switch

## System overview

The LECTUS duo 3000 DESFire EV1 line consists of two readers for MIFARE classic and EV1 cards and transponders. They support the data record of Bosch coded MIFARE credentials and the CSN of ISO14443A cards as well.

Both readers provide a 26 Bit Wiegand and RS485/OSDP host interface, selectable easily by DIP switch. When operating in RS485/OSDP mode up to eight readers can be connected to a respective controller, e.g. AMC2-4R4. Reader address is settable via four DIP switches individually. Running in that mode readers can be easily supervised.

Three LED indicators and a beeper give clear feedback to the user during operation. The reader's logo is illuminated in the dark. The reader is IP65 rated and fits for indoor and outdoor use.

## Technical specifications

### Electrical characteristics

Input voltage	8.5 V to 16 Vdc – max. 18 Vdc
Current draw	65 mA @ 12 Vdc Max.: 130 mA @ 12 Vdc

### Operational Characteristics

Tamper output	Open collector, active low, 32 mA max sink current. Optical Technology
Wiegand D0 output	5 V (TTL)
Wiegand D1 output	5 V (TTL)
Green LED control input	Active low
Red LED control input	Active low
Buzzer control input	Active low
RS485	OSDP protocol
Wiegand IF	D0/D1 Wiegand protocol
Keypad	LECTUS duo 3000 E: none LECTUS duo 3000 EK: 2x6

### Environmental Characteristics

Operating environment	Indoor and outdoor use - all weather.
Operating temperature	-25 °C to 65 °C (-13 °F to 150 °F)
Operating humidity	0 to 95% (Non-condensing)

IP rating	IP65
UV-light resistant	Yes

**MIFARE & Cards Specification**

Read range - ISO cards	> 3 cm (1.18 in.)
Key fob	> 2 cm (0.78 in.)
Supported cards	MIFARE 13.56 MHz ISO 14443 Type A
Anti-Collision support	Yes
NXP Chips supported	MF3ICD21 - 2K MF3ICD41 - 4K MF3ICD81 - 8K

**MIFARE MAD, CSN Support**

The reader follows the MAD rules	
Reads INIT CSN	Yes
Reads CSN after non-detection of MAD information	Yes

**Physical Characteristics**

Dimensions (L x W x D)	137 mm x 44 mm x 27.5 mm (5.39 in. x 1.73 in. x 1.08 in.)
Weight	Approx. 220 g (0.5 lb)

**Ordering information****LECTUS duo 3000 E**

Proximity reader supporting data record of Bosch coded MIFARE classic and DESFire EV1 cards and keyfobs and CSN of ISO14443A credentials, providing RS485/OSDP and 26 Bit Wiegand interface on same device, IP65 rated for indoor and outdoor use, wall or mullion mount.

Order number **ARD-AYBS6280**

**LECTUS duo 3000 EK**

Proximity reader supporting data record of Bosch coded MIFARE classic and DESFire EV1 cards and keyfobs and CSN of ISO14443A credentials, providing RS485/OSDP and 26 Bit Wiegand interface on same device, IP65 rated for indoor and outdoor use, wall or mullion mount, 2x6 keypad.

Order number **ARD-AYBS6380**

**Represented by:**

**North America:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**  
Bosch (Shanghai) Security Systems Ltd.  
203 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**Latin America and Caribbean:**  
Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com