

# ALTV615DC8220 Series

## DC CCTV Power Supplies

Altronix ALTV615DC8220 Series power supplies are designed with eight (8) individual fuse or PTC protected outputs for powering CCTV cameras and other video accessories. They provide 6VDC-15VDC with a total of up to 4A continuous supply current.



ALTV615DC8220

### Key Features

- Eight (8) fuse or PTC protected outputs
- 6-15VDC field adjustable output voltage
- Filtered and electronically regulated outputs
- Short circuit and thermal overload protection
- AC Input and DC Output LED indicators
- Spare fuses provided
- Lifetime Warranty

### ALTV615DC8220 Series Power Supply Configuration Reference Chart

Altronix Model Number	Output Voltage	Total Output Current (Power)	Number of Outputs	PTC Protected Outputs (auto-resettable)	Fuse Protected Outputs	Output Current (max per output)	220VAC 50/60Hz Input Current
ALTV615DC8220	6-15VDC	4A	8	-	✓	3.5A	0.5A
ALTV615DC8CB220				✓	-	2.5A	

### Specifications

<b>Input</b>		<b>Physical and Environmental</b>	
Voltage	220VAC (working range 198VAC-256VAC), 50/60Hz, 0.5A	<b>Dimensions (H x W x D):</b>	
<b>Outputs</b>		Enclosure:	
Voltage	6-15VDC	13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)	
Current	Up to 4A	Shipping:	
<b>Indicators (LED)</b>		15" x 13.875" x 4.75" (381mm x 352.4mm x 120.6mm)	
Input	LED	<b>Weight (approx.)</b>	
Output	LED	Product Weight	11.5 lb. (5.22 kg)
		Shipping Weight	12.0 lb. (5.44 kg)
		<b>Temperature</b>	
		Operating:	0°C to 49°C (32°F to 120°F)
		Storage:	- 20°C to 70°C (- 4°F to 158°F)
		Relative Humidity	85% +/- 5%
		BTU/Hr. (approx.):	12-31 BTU/Hr., depending on output

#### Lifetime Warranty