

## MaximalRD Series

### Rack Access Power Controllers (PTC)



Maximal Rack Mount Series units distribute and switch power to access control systems and accessories. They convert a 115VAC 50/60Hz input into eight (8) or sixteen (16) independently controlled 12VDC and/or 24VDC PTC protected outputs. Outputs are activated by an normally open (NO) or normally closed (NC) dry trigger input from an Access Control System, Card Reader, Keypad, Push Button, PIR, etc. Units will route power to a variety of access control hardware devices including: Mag Locks, Electric Strikes, Magnetic Door Holders, etc. Outputs will operate in both Fail-Safe and/or Fail-Secure modes. The FACP Interface enables Emergency Egress, Alarm Monitoring, or may be used to trigger other auxiliary devices. The fire alarm disconnect feature is individually selectable for any or all of the outputs.



Maximal3RHD

### Key Features

- Eight (8) or Sixteen (16) independently controlled PTC protected 12VDC and/or 24VDC outputs
- Individually selectable Mag Lock/Strike (Fail-Safe, Fail-Secure) solid state PTC protected outputs
- Thermal and short circuit protection with auto reset
- Supervision:
  - AC Fail
  - Low Battery
- Fire Alarm disconnect (latching or non-latching) is individually selectable for any or all of the outputs
- Fire Alarm disconnect input options:
  - a) Normally open (NO) or normally closed (NC) dry contact input
  - b) Polarity reversal input from FACP signaling circuit
- Built-in charger for sealed lead acid or gel type batteries
- Instantaneous transfer to stand-by batteries
- Lifetime Warranty

### MaximalRD Power Supply Series Configuration Reference Chart

Altronix Model Number	115VAC 50/60Hz Input Current	Power Supply Board Input Fuse Rating	Power Supply 1 (8 outputs)	Power Supply 2 (8 outputs)	Total Output Current	PTC Protected Auto-Resettable Outputs	Maximum Current Per ACM8CBR-M Output
Maximal1RHD	1.9A	5A/250V	12VDC @ 4A	N/A	4A	8	2.5A
			24VDC @ 3A	N/A	3A		
Maximal1RD	1.9A	5A/250V	12VDC @ 4A	N/A	4A	16	2.5A
			24VDC @ 3A	N/A	3A		
Maximal3RHD	1.9A	3.5A/250V	12VDC @ 6A	N/A	6A	8	2.5A
			24VDC @ 6A	N/A			
Maximal3RD	1.9A	3.5A/250V	12VDC @ 6A	N/A	6A	16	2.5A
			24VDC @ 6A				
Maximal33RD	3.8A	3.5A/250V	12VDC @ 6A	12VDC @ 6A	12A	16	2.5A
			24VDC @ 6A	24VDC @ 6A			
			12VDC @ 6A	24VDC @ 6A			

### Lifetime Warranty

## MaximalRD Series

Rack Access Power Controllers (PTC)



### Specifications

#### Input

Voltage	115VAC, 50/60Hz
Fusing	Varies, See Reference Chart

#### Outputs

Voltage	12VDC and/or 24VDC, see Reference Chart
Current	Varies, see Reference Chart
Protection	PTC 2.0A
Other	Overvoltage protection Filtered and regulated outputs

#### Back-up Battery *(separate enclosure is required)*

Type	Sealed lead acid or gel type
Fuse Rating	15A/32VDC (Maximal1RHD and Maximal1RD); Maximal3RHD, Maximal3RD and Maximal33RD do not have a battery fuse
Failover	Upon AC loss, instantaneous

#### Fire Alarm Disconnect

Supervised	Latching or non-latching, individually selectable for any or all of the outputs
------------	---

#### Supervision

AC Failure	Form "C" contacts
Battery	Form "C" contacts

#### Indicators (LED)

Input	Illuminated ON/Reset Switch
Output	Individual Output Status LEDs located on the front panel

### Physical and Environmental

2U rack mount chassis for use in standard EIA 19" rack.

#### Dimensions (H x W x D):

Enclosure:	3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
Shipping:	20.25" x 12.5" x 7.25" (514.4mm x 317.5mm x 184.2mm)

#### Weight (approx.):

Model	Product Weight	Shipping Weight
Maximal1RHD	10.7 lb. (4.85 kg)	12.7 lb. (5.76kg)
Maximal1RD	10.7 lb. (4.85 kg)	12.7 lb. (5.76kg)
Maximal3RHD	10.85 lb. (4.92 kg)	12.85 lb. (5.83 kg)
Maximal3RD	10.85 lb. (4.92 kg)	12.85 lb. (5.83 kg)
Maximal33RD	12.4 lb. (5.62 kg)	14.3 lb. (6.49 kg)

#### Temperature

Operating:	0°C to 49°C (32°F to 120°F)
Storage:	- 20°C to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%

#### BTU/Hr. (approx.)

Model	12VDC	24VDC	12 and 24VDC
Maximal1RHD	25	37	N/A
Maximal1RD	25	37	N/A
Maximal3RHD	37	74	N/A
Maximal3RD	37	74	N/A
Maximal33RD	74	141	106

### Accessories (order separately)



#### RE2 – Rack Mount Battery Enclosure

- Accommodates up to four (4) 12VDC/7AH batteries

#### Lifetime Warranty