

## **AP-2**

## 2 ZONE AUDIO BASE STATION **TECHNICAL DATA SHEET**

#### **DESCRIPTION**

The AP-2 is a two-zone audio base station. It is designed for audio monitoring and interfacing with DVR's, VCR's or other audio devices that accept line level input. The unit is a desk top audio base station that contains a 3" speaker for monitoring live audio and playback from a DVR or VCR. AP-2 will accommodate 2 microphones and zone selection is by pushbutton. Contains Mute/Playback switch that mutes audio from remote microphones.



AP-2 Audio **Base Station** 

### **AP-2 ACCESSORIES**

- Model AD-1 12Vdc power supply
- Dual RCA cables for connection to DVR/VCR

Model AP-2 Base Station can be equipped for 19"

rack mounting. Request AP-2-RM

### **APPLICATION**

The AP-2 is designed for numerous applications such as:

- Convenience Stores Sleep Disorder Centers
- Fast Food Restaurants Speech Therapy Labs
- Booking Rooms
- Cashier Booths
- Interrogation Rooms Day Care Centers
- Car dealership sales contract rooms
- Child Abuse Interviews

# Audio output (RCA) to DVR, VCR

- Lighted zone and playback/mute switches
- 3" speaker for monitoring live audio and playback from a DVR or VCR
- 3.5 mm headphone jack for private listening
- Has Mute switch to prevent audio from being heard at the unit speaker
- 2 Line level microphone outputs

#### WIRING REQUIREMENTS

2 Conductor shielded cable, 22 gauge with a 24 gauge drain wire



## NOTE: Unshielded cable is not satisfactory for audio systems



### IMPORTANT NOTICE When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped. Federal Law References: Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.

### **SPECIFICATIONS**

Monitor power output	1W @ 8Ω
Audio output impedance	1ΚΩ
Audio input impedance	10kΩ
Freq. response	100 Hz to 10kHz
Headphone impedance	8 to 600Ω
Current Drain	200mA
Power input	12 Vdc, 500mA
Dimensions	6 5/8"W x 8 5/8"L x 2 1/8"H
Weight	1lb 5 oz
Shipping Weight	3 lbs