

techsupport@louroe.com / www.louroe.com

AP-4-RM

4 ZONE RACK MOUNTED AUDIO BASE STATION TECHNICAL DATA SHEET

DESCRIPTION

The AP-4-RM is a rack mounted four- zone audio base station designed to interface with a DVR, VCR or other recording devices that accept line level input. The AP-4-RM Audio Base Station contains a built-in 3" speaker and volume control for producing live audio and audio playback. Has mute switch to mute audio from being heard at the speaker.



AP-4-RM Audio Base Station



CONTENTS

AD-1 Power Supply

AP-4-RM (Listed Audio Base Station (Rack Mounted

AD-1 UL Listed AC ADAPTER

Dual RCA Cable

APPLICATION

The AP-4-RM is designed for numerous applications such as:

Convenience Stores Sleep Disorder Centers

Fast Food Restaurants Speech Therapy Labs

Booking RoomsCashier Booths

Interrogation Rooms
Casino use in:

Car dealership sales - soft count rooms

contract rooms - detention centers

- medical treatment rooms
- Child Abuse Interviews - cash cages

FEATURES

- Audio output (RCA) to DVR, VCR
- 3" speaker for monitoring live audio and playback from a DVR or VCR
- 3.5 mm headphone jack for private listening
- Mute switch to mute audio from being heard at the speaker
- Overload LED to indicate short in wiring connections
- 4 Line level microphone outputs

SPECIFICATIONS

Monitor power output	1W @ 8Ω
Audio output impedance	1ΚΩ
Audio input impedance	10kΩ
Freq. response	100 Hz to 10kHz
Headphone impedance	8 to 600Ω
Current Drain	200mA
Power input	12 Vdc, 500mA
Dimensions	19"L x 3 1/2"W x 8 5/8"D
Weight	2 lbs 13.5 oz
Shipping Weight	4 lbs

WIRING REQUIREMENTS

2 Conductor **shielded** cable, 22 gauge with a 24 gauge drain wire.

NOTE: Unshielded cable is not

satisfactory for audio

systems.

West Penn 452 or equivalent