

AOP-SP-CF/AOP-SP-CS

SPEAKERPHONE TECHNICAL DATA SHEET

6955 VALJEAN AVE, VAN NUYS, CA 91406 PH: (818)994-6498 / FAX: (818)994-6458 techsupport@louroe.com / www.louroe.com

DESCRIPTION

Model AOP-SP-CF and AOP-SP-CS are ceiling mount speakerphones designed to interface with various modes of audio/video transmission systems. They provide bi-directional audio with the receiving source (DVR, PC soundcard, IP network cameras with audio and video servers with audio, etc). Both AOP-SP-CF and AOP-SP-CS contain a built-in electret condenser microphone and a 4" speaker. Also a control potentiometer for adjusting the sensitivity of both transmitted and received audio.

AOP-SP-CF is for Flush mounting to ceiling AOP-SP-CS is for Surface mounting to ceiling

APPLICATION

Model AOP-SP-CF and AOP-SP-CS have the electronics to provide two-way/talk-listen audio with the following transmission systems:

- DVR's
- IP Network Cameras
- PC Soundcards
- Video Servers

WIRING REQUIREMENTS

3 Conductor consisting of:

- 2 Conductor shielded, 20 gauge with 22 gauge drain
- 1 Conductor unshielded, 20 gauge All in the same jacket





IMPORTANT NOTICE When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped. Federal Law References: Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.





MODEL AOP-SP-CF 2-way Speakerphone Ceiling Mount-Flush

MODEL AOP-SP-CS 2-way Speakerphone Ceiling Mount-Surface

FEATURES

- Omni-directional microphone and 4" speaker
- Controls for adjusting volume of both listen and talkback
- Flush or surface ceiling mount models
- Hands-free operation for talk/listen
- Muting circuit to minimize echo

SPECIFICATIONS (Microphone)

Electret Condenser	
Line level (0 dB @ 600Ω)	
unbalanced	
-45 dB	
40 Hz - 15 kHz	
600Ω	

SPECIFICATIONS (Speaker)

Speaker power output	1W
Speaker impedance	8Ω
Speaker magnet	1.73 oz ceramic
Speaker size	4" (102mm)
Current Drain	200mA
Supply Voltage	12Vdc

SPECIFICATIONS (Mechanical)

AOP-SP - CF/CS (grill)	12 7/8"
ERD-8 (Backbox for AOP-SP-CF)	12 1/4" Dia x 4" D
MR-8 (Mounting ring for AOP-SP-CS) 12 3/8" Dia x 3" D
Weight (AOP-SP-CS)	2 Lbs 12 oz
Weight (AOP-SP-CF)	2 Lbs 12 oz
Weight, (AOP-SP-CS) with MR-8	5 Lbs (2.3 Kg)
AOP-SP-CF Shipping Weight	7 lbs
AOP-SP-CS Shipping Weight	7 lbs