

techsupport@louroe.com / www.louroe.com

ASK-4°#101B

AUDIO MONITORING SYSTEM TECHNICAL DATA SHEET

DESCRIPTION

The ASK-4[®] #101B is a single zone audio monitoring system. It is designed for audio monitoring and interfacing with DVR's, VCR's or other audio devices that accept line level input. The microphone can be ceiling or wall mounted and provides a 30 foot diameter circle coverage. The mic element is exteded 3' for high ceiling application. The desk top audio base station (APR-1) contains a 3" speaker for monitoring live audio and playback from a DVR or VCR. Microphone is preamplified and produces line level output.

KIT CONTENTS

- VERIFACT[®] Model B Electret Condenser Microphone for surface mounting to ceiling
- Model APR-1 Audio Base Station
- Model AD-1 12Vdc power supply
- Dual RCA cables for connection to DVR/VCR

Model APR-1 Base Station can be equipped for 19" rack mounting. Request RM-1935-APR Rack Mount Assembly

APPLICATION

The ASK-4[®] #101-B is designed for numerous applications such as:

Convenience Stores Sleep Disorder Centers

■ Fast Food Restaurants ■ Speech Therapy Labs

Booking Rooms

Cashier Booths

Interrogation Rooms

Casino use in:

Car dealership sales contract rooms

- soft count rooms
- detention centers
- medical treatment rooms
- Child Abuse Interviews cash cages

WIRING REQUIREMENTS

2 Conductor shielded cable, 22 gauge with a 24 gauge drain wire

NOTE: Unshielded cable is not satisfactory for audio systems





IMPORTANT NOTICE When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.

Federal Law References:
Federal Regulations, US Code, Title 18. Crime and Criminal
Procedure, Sec 2510.



- Audio output (RCA) to DVR, VCR
- Omni-directional microphone can pick up normal sounds 15' away if wall mounted, or within a 30' diameter circle if ceiling mounted
- 3" speaker for monitoring live audio and playback from a DVR or VCR
- 3.5 mm headphone jack for private listening
- Microphone may be mounted up to 1000' from the APR-1Base Station

SPECIFICATIONS (Microphone - Model B)

■ Type	Electret Condenser
Output	Line Level (0 dBV, 600Ω @ 1 kHz)
Frequency response	50 Hz to 15 kHz
Current drain	10 mA
Supply voltage	12Vdc
Dimensions	4"Dia x 1 ½"H
Weight	3.5 oz

SPECIFICATIONS (Base Station - APR-1)

Monitor output power	1W@8Ω
Audio output impedance	600Ω @ 1kHz
Audio input impedance	10ΚΩ
Freq. response	100 Hz to 10 kHz
Headphone impedance	8 to 600Ω
Power supply	12 Vdc, 500 mA
Dimensions	8 ¼"L x 5 ¾"W x 1 3/8" H
Weight	1 lb 6 oz
Shipping Weight of kit	3 lbs