

# **SQP133**



#### Introduction

SQP133 is a dynamic digital signage with a 13.3-inch monitor, designed to display slideshows made of images and videos. The device is available in black or white color.

### **Key Features**

- Multimedia support
- Panel resolution of 1280 x 800
- Content Schedule and Content Designer
- Content management system (CMS Server and CMS Lite)
- IR remote control
- Wireless connectivity (WiFi USB Adaptor required)
- Built-in speaker
- SD/SDHC card and USB storage

# **CMS**





**CMS Server** 

**CMS Lite** 

### **Authoring Tool**





**Content Designer** 

**Content Schedule** 

# **Compatible Firmware and Software Versions**

|   | SQP133           |
|---|------------------|
| CMS Server / CMS Lite V1.0.4.0            | V1.06            |
| CMS Server / CMS Lite V1.0.3.0            | V1.05            |
| CMS Server / CMS Lite V1.0.2.0 or earlier | V1.04 or earlier |
| Content Designer V1.0.5.0 or later        | V1.05 or later   |
| Content Designer V1.0.4.0 or earlier      | V1.04 or earlier |

SQP133 July 28, 2016

<sup>\*</sup> No SD/SDHC card slot & local storage function for Argentina




# **SPECIFICATIONS**

| Model                  | SQP133  |
|------------------------|---|
| Video Format           | Multimedia Support  |
| Audio Format           | AAC   |
| Photo Format           | PNG / JPEG / BMP  |
| Audio Output           | Built-in speaker (4 ohm / 1.5 W)  |
| Video Output           | 1280 x 800  |
| TV Standard            | NTSC / PAL  |
| SD/SDHC Card           | Class 4 or above (FAT32 and NTFS formats)   |
| USB                    | USB 2.0 Backward Compatible (FAT32 and NTFS formats)  |
| IR Remote Control      | Yes   |
| Power Adapter          | 12V / 3A DC Jack (Max. 36 W)  |
| Operating Temperature  | 0 °C ~ 40 °C / 32 °F ~ 104 °F   |
| Operating Humidity     | 20 % ~ 80 % (with no condensation)  |
| Dimensions (W x H x D) | 342.8 × 220.3 × 38.3 mm / 13.5 x 8.7 x 1.5 in   |
| Net Weight             | 1160 g / 2.6 lb   |
| Housing                | Black / White   |
| Language               | English / French / German / Italian / Japanese / Portuguese / Russian / Spanish / Traditional Chinese |

**Note:** Specifications are subject to change without notice.

# **Overview**







| No | Name         |
|----|--------------|
| 1  | MENU         |
| 2  | ENTER        |
| 3  | UP           |
| 4  | DOWN         |
| 5  | LEFT         |
| 6  | RIGHT        |
| 7  | STAND BY     |
| 8  | Power OFF/ON |
| 9  | DC 12V       |

SQP133 July 28, 2016

July 28, 2016



# **Accessory**

| Name                                | Details  |
|-------------------------------------|--|
| "                                   | The WiFi USB Adapter is designed to connect the digital signage device to the wireless network.  This product complies with IEEE 802.11 b/g/n (Draft 3.0) standards for wireless networking. |
| WiFi USB Adapter                    |  |
|                                     | The USB dongle can provide the Hardware Watchdog function to the system by restarting the  |
| Internal GV-USB Dongle for CMS Lite | computer when Windows crashes. You need to connect the dongle internally on the motherboard.   |
| and CMS Server                      |  |

# **Packing List**

- SQP133 device × 1
- IR remote control × 1
- Magnetic hinge x 1
- Screw x 4
- AC/DC adaptor × 1 (12 V, 3 A, 36 W)
- Software DVD x 1

SQP133