

CLR-XVR8-5MP



- 8 BNC Video Inputs Supporting AHD, TVI, CVI and CVBS
- Supports Additional 4 IP Cameras
- H.264 Video Compression
- Up to 5MP Recording Resolution for HD Analog and up to 4MP for IP Cameras
- 1 HDMI, 1 VGA and 1 CVBS BNC Video Output
- 1 SATA Interface for Internal Storage
- 1 RJ-45 10/100M Ethernet Interface
- Supports NAT functionality and QRCode scanning for mobile device access

Technical Specifications

CLR-XVR8-5MP	
Video Input Interface	8 BNC Video Inputs
Video Input Signal	AHD, TVI, CVI, CVBS
IP Input Bandwidth	4 IP Cameras with 24Mbps Recording Bandwidth
Video Output Interface	1 HDMI: 3840 x 2160; 1920 x 1080; 1280 x 1024 1 VGA: 1920 x 1080; 1280 x 1024 1 CVBS (BNC); Spot Monitor
Audio Input Interface	1 Channel, RCA Audio Input
Audio Output Interface	1 Channel, RCA Audio Output
Two-way Audio	1 Channel, RCA Audio Input (Uses Channel 1 Audio Input)
HD Analog Recording Resolution	5MP, 4MP, 3MP, 1080p, 720p, WD1
HD Analog Recording Frame Rate	5MP@10fps 4MP / 3MP@15fps 1080p / 720p / WD1@30fps
Bit Rate	768Kbps - 8Mbps
IP Recording Rate	4MP / 3MP / 1080p, 960p, 720p@30fps
Simultaneous Playback	Maximum 8 channels
Alarm Inputs	n/a
Relay Outputs	n/a
Network interface	1 x 10/100M RJ-45 Ethernet Interface
Remote Connections	5 Remote Users Maximum
HDD Interfaces	1 SATA Interface, Maximum 8TB
Backup Media	External USB or Network Download
USB Interfaces	1 x USB2.0 (Front), 1 x USB3.0 (Rear)
RS-485 Interface	1 Port for Serial PTZ Control
Power Supply	DC12V3A External Power Adapter
Power Consumption	< 10W (Without HDD)
Operating Environment	14° - 122°F, less than 90% Relative Humidity
Dimensions	11.8" x 9.8" x 2"
Weight (without HDD)	~9lbs