

CLR-XVR8



- 8 BNC Video Inputs Supporting AHD, TVI, CVI and CVBS
- Supports 1 IP Camera input up to 3MP Resolution
- H.264 Video Compression
- Up to 1080p Recording Resolution for HD Analog and up to 3MP for IP Camera
- 1 HDMI, 1 VGA and 1 CVBS BNC Video Output
- 1 SATA Interface for Internal Storage up to 6TB
- 1 RJ-45 10/100M Ethernet Interface
- Supports NAT functionality and QRCode scanning for mobile device access



Technical Specifications

CLR-XVR8	
Video Input Interface	8 BNC Video Inputs
Video Input Signal	AHD, TVI, CVI, CVBS
IP Input Bandwidth	1 IP Camera @6Mbps
Video Output Interface	1 HDMI, 1 VGA, 1 CVBS (BNC)
Display Resolution	1920 x 1080; 1280 x 1024
Audio Input Interface	4 Channel, RCA Audio Inputs
Audio Output Interface	1 Channel, RCA Audio Output
Two-way Audio	1 Channel, RCA Audio Input (Uses Channel 1 Audio Input)
Recording Resolution	1080p, 1080p lite, 720p WD1
Frame Rate	1080p: 120fps (NTSC) / 1080p lite, 720p, WD1: 240fps (NTSC)
Bit Rate	768Kbps - 8Mbps
IP Recording Rate	3MP@15fps / 1080p, 960p, 720p@30fps
Simultaneous Playback	Maximum 8 channels
Alarm Inputs	4 Channels
Relay Outputs	1 Channels
Network interface	1 x 10/100M RJ-45 Ethernet Interface
Remote Connections	5 Remote Users Maximum
HDD Interfaces	1 SATA interface, maximum 6TB
Backup Media	External USB or Network Download
USB Interfaces	2 x USB2.0 (1 Front, 1 Rear)
RS-485 Interface	1 Port for Serial PTZ Control
Power Supply	DC12V External Power Adapter
Power Consumption	< 8W (Without HDD)
Operating Environment	14° - 122°F, less than 90% Relative Humidity
Dimensions	11.8" x 10.6" x 2.2"
Weight (without HDD)	~9lbs