

CLR-4KNVR432-P

Technical Specifications



Model	
CLR-4KNVR432-P	
IP Camera Inputs	32 Channels
Video Output Interface	1 HDMI, 1 VGA
Display Resolution	HDMI: 4K (3840 x 2160); 1920 x 1080; 1280 x 1024
	VGA: 1920 x 1080; 1280 x 1024
Audio Output Interface	1 Channel, RCA Audio Output
Two-way Audio	1 Channel, RCA Audio Input
Recording Resolution	8MP / 5MP / 4MP / 3MP / 1080p / 960p / 720p
Recording Bandwidth	256Mbps
Simultaneous Playback	Maximum 16 channels
Alarm Inputs	16 Channels
Relay Outputs	4 Channels
Network interface	1 x 10/100/1000M RJ-45 Ethernet Interface
PoE Ports	16 x 10/100M RJ-45 PoE Ports
Remote Connections	10 Concurrent Remote Users Maximum
HDD Interfaces	4 SATA interface, maximum 6TB
Backup Media	External USB or Network Download
USB Interfaces	2 x USB2.0 (1 Front, 1 Rear)
Power Supply	Internal ATX Power Supply
Power Consumption	< 30W (Without HDD)
Operating Environment	14" - 122" F, less than 90% Relative Humidity
Dimensions	17.3" x 15.3" x 2.75"
Weight (without HDD)	~15lbs

- 32 IP Channel Inputs •
- 16 Independent 10/100M PoE Ports •
- H.265 / H.264 Video Compression •
- Up to 8MP Recording Resolution •
- 1 RJ-45 10/100/1000M Ethernet Interface •
- 1 HDMI (Up to 4K Resolution) and 1 VGA Output •
- 4 Sata Interface for Internal Storage up to 6TB Each •
- Supports NAT functionality and QR Code Scanning for Mobile Device Access •
- ONVIF Compliant •