

CLR-4KNVR832-P

Technical Specifications



Model	
CLR-4KNVR832-P	
IP Camera Inputs	32 Channels
Video Output Interface	1 HDMI, 1 VGA
Display Resolution	HDMI: 4K (3840 x 2160); 1920 x 1080; 1280 x 1024
	VGA: 1920 x 1080; 1280 x 1024
Audio Output Interface	1 Channel, RCA Audio Output
Two-way Audio	1 Channel, RCA Audio Input
Recording Resolution	8MP / 5MP / 4MP / 3MP / 1080p / 960p / 720p
Recording Bandwidth	256Mbps
Simultaneous Playback	Maximum 16 channels
Alarm Inputs	16 Channels
Relay Outputs	4 Channels
Network interface	1 x 10/100/1000M RJ-45 Ethernet Interface
PoE Ports	16 x 10/100M RJ-45 PoE Ports
Remote Connections	10 Concurrent Remote Users Maximum
HDD Interfaces	8 SATA interface, maximum 6TB
Backup Media	External USB or Network Download
USB Interfaces	2 x USB2.0 (1 Front, 1 Rear)
Power Supply	Internal ATX Power Supply
Power Consumption	< 30W (Without HDD)
Operating Environment	14" - 122" F, less than 90% Relative Humidity
Dimensions	16.9" x 17.7" x 3.5"
Weight (without HDD)	~24bs

- 32 IP Channel Inputs
- 16 Independent 10/100M PoE Ports
- H.265 / H.264 Video Compression
- Up to 8MP Recording Resolution
- 1 RJ-45 10/100/1000M Ethernet Interface
- 1 HDMI (Up to 4K Resolution) and 1 VGA Output
- 8 Sata Interface for Internal Storage up to 6TB Each
- 1 eSATA Interface
- Supports NAT functionality and QR Code Scanning for Mobile Device Access
- ONVIF Compliant