Comcast SMC Router Port Forwarding Setup for Geovision DVR

- 1. Login into your Comcast SMC router by typing the following gateway into a web browser http://10.1.10.1 [By Default Username: **cusadmin** password: **highspeed**]
- 2. Click "Firewall" > "Port Forwarding" > "Add New "

MAIN	Firewall	Port	Web Site	DMZ	1-to-1	
FEATURE SETTINGS	options	Configuration	вюскіпд		NAT	
Administration	Port Forwarding Port Triggering Port Blocking True Static IP Port Management					
LAN	TRUE OF	TTO TO DODT NAM	LOCHENT			
Firewall	True Static IP Port Management is used to allow certain inbound traffic to specific					
Gateway Summary	computers	on the true static II	P network. Ports	are manag	ed using logical	port
HELP	numbers a	nu ir auuresses.			No.	
	add new	edit de	lete			

3. Now fill in the below:

Application Name: Geovision DVR 1 Port Range: 80 Protocol: Both IP Address: IP Address of the Geovision DVR

Do this for ports 80, 4550, 5550, 8866, 5511 and name each application differently. Example – Geovision DVR 1, Geovision DVR 2, etc. (**Note**: Each application must be uniquely named or else it will not work)

4. Press the **"Apply"** button to save the settings.