



NVR302-E-P Series Network Video Recorder



Features:

8/16-channel input

Third-party IP cameras supported with ONVIF conformance
Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution

Up to 12 megapixels resolution recording

Support H.265/H.264 video formats

Accurate retrieval, instant playback

2 SATA HDD up to 12TB

Plug & play with up to 8 independent PoE network interfaces

Support for P2P, UPnP, NTP, DHCP, PPPoE

Support for mobile client access

NVR302-E-P Series

Network Video Recorder

Video and Audio	NVR302-08E-P8	NVR302-16E-P8	NVR302-16E-P16
IP Video Input	8-ch	16-ch	16-ch
Two-way Audio Input	1-ch, RCA		
Network			
Incoming Bandwidth	80 Mbps	160 Mbps	160 Mbps
Outgoing Bandwidth	160 Mbps	320 Mbps	320 Mbps
Remote Connection	128		
Video/Audio Output			
HDMI/VGA Output	VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz		
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Audio Output	1-ch, RCA		
Synchronous Playback	8-ch	16-ch	16-ch
Decoding			
Compression	H.265/H.264		
Live View/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Capacity	4 x 12MP@20, 4 x 4K@30, 8 x 4MP@20, 16 x 1080p@25, 32 x 720p@25		
Hard Disk			
SATA	2 SATA interfaces		
Capacity	Up to 6 TB for each disk		
External Interface			
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet interface		
Network Function	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P		
Serial Interface	1 x RS-485		
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0		Front panel: 1x USB2.0, Rear panel: 1 x USB3.0, 1 x USB2.0
Alarm In	4-ch		
Alarm Out	1-ch		
PoE			
Interface	8 independent 100 Mbps PoE network interfaces		16 independent 100 Mbps PoE network interfaces
Supported Standard	IEEE 802.3af/at		
General			
Power	100-240 V AC		
Consumption(without HDD and PoE)	≤ 20 W		
PoE	Max 30W for single port, max 200W in total (12.5W for each)		
Working Temperature	-10°C ~ + 55°C (+14°F ~ +131°F)		
Working Humidity	10% ~ 90%		
Dimensions	49 × 380 × 315mm		
Weight(without HDDD)	2.48 Kg		

*Product specifications and availability are subject to change without notice.

Zhejiang Uniview Technologies Co., Ltd.
Address: Building No.10, Wanlun Science Park, Jiangling Road 88, Hangzhou, P. R. China, 310051
Website: www.uniview.com Email: overseasbusiness@uniview.com

©2016 Zhejiang Uniview Technologies Co., Ltd. all rights reserved.
2016.07-OM-160144-OWN V1.0

